

08-624564




Fig. 1
Prior Art





Fig. 2
Prior Art



20

Fig. 3
Prior Art

08-624584





Fig. 4


Principle of Channel Segmentation (Transmit mode - Tx)



- Digitally controlled analog switch (on/off)
Signal path may be interrupted to limit distribution over network at 3 points per crosspoint switch (up, down, across)


Fig. 5

Principle of Channel Segmentation (Receive mode - Rx)



- Digitally controlled analog switch (on/off)
Signal path may be interrupted to limit distribution over network at 3 points per crosspoint switch (up, down, across)

Fig. 6



08-624,504

User input
Paths

پاکستانی
عمرانی
2006ء

卷之三

08-624504




FIG. 7A

08-624864





Fig. 8

08-624564



၁၀




Fig. 10

Twisted Pair Termination Module




Figure 11





Fig. 12

FSK C - FREQUENCY SHIFT KEY COUPLER
 FSK S - FREQUENCY SHIFT KEY SEPARATOR
 IR - INFRA RED DETECTOR
 RS-232A - SERIAL COMMUNICATIONS PORT
 RS-232B - SERIAL COMMUNICATIONS PORT
 TP TM - TWISTED PAIR TERMINATION MODULE



Eig 13

08-624, S04




FIGURE 14-15

FM H : Frequency Modulators
FM D : Frequency Demodulators
FSK H : Frequency Shift Keying Modulator
FSK D : Frequency Shift Keying Demodulator
FC : Frequency coupler
FS : Frequency Separator
DIGITAL BUS : CPU Interface with the Central Processor Unit
SCC : Serial Communication Control
AE TPIN : Auto-equalized Tilted Polarization
RS 232 : Low Speed Serial Communication
CH UP : Up Channel Backbone Port
CH DOWN : Down Channel Backbone Port

08-624 564







FIGURE 15



08-60245204




08-624584



BIPOL : Bidirectional Twisted Pair Line Interface


08-624564



08-624564



RECEPTION PORTION OF TWISTED
PAIR TERMINATION MODULE

RECURE
20




FREQUENCY
SEPARATOR
350

5V0
FSK2
REJECTION




857

SINE WAVE TO DC LEVEL CONVERTER
(FSK2 DEMODULATOR)




ANALOG TO DIGITAL
CONVERSION
714

CPU



08-624 564



22


FIGURE

08-624564

S3IC2

FIGURE

23



FM H : Frequency Modulator

FM D : Frequency Demodulator

FSK H : Frequency Shift Keying Modulator

FSK D : Frequency Shift Keying Demodulator

FC : Frequency Coupler

FS : Frequency Separator

DIGITAL BUS : CPU Interface with Digital Devices.

SCC : Serial Communication Controller


AE TPM : Auto-Equalized Twisted Pair Termination Module

RS 232 : Low Speed Serial Communication Port

CH UP : Up Channel Backbone Port

CH DOWN : Down Channel Backbone Port

08-624584




FIGURE

24

- FM N : Frequency Modulators
- FM D : Frequency Demodulators
- DIGITAL BUS : CPU Interface with Digital Devices
- SCC : Serial Communication Controller
- FSK N : Frequency Shift Keying Modulator
- FSK D : Frequency Shift Keying Demodulator
- FC : Frequency coupler
- FS : Frequency separator
- AE TPM : Auto-EQUALIZED Twisted Pair Termination Module
- RS 232 : Low-Speed Serial Communication Port
- CH UP : Up Channel Backbone Port
- CH DOWN : Down Channel Backbone Port

88-624564



FM N : Frequency Modulators
 FM D : Frequency Demodulators
 FSK N : Frequency Shift Keying Modulator
 FSK D : Frequency Shift Keying Demodulator
 FC : Frequency Coupler
 FS : Frequency Separator
 DIGITAL BUS : CPU Interface with Digital Devices
 SCC : Serial Communication Controller
 DMI : Digital Matching Interface
 AE TPM : Auto-Equalized Twisted Pair Termination Module
 RS 232 : Low Speed Serial Communication Port
 CH UP : Up Channel Backbone Port
 CH DOWN : Down Channel Backbone Port

FIGURE

25